



JDB650 固体镶嵌型自润滑轴承 JDB650 Solid-lubricants Inaid Bushings

I.D. Φd 内径 F7	O.D. ΦD 外径 m6	L -0.10 -0.30												装压后内孔
		30	35	40	50	60	70	80	100	120	130	140	150	
50 +0.050 +0.025	62 +0.030 +0.011	●	●	●	●	●	●							+0.045 +0.020
50 "	65 "	●		●	●	●	●	●	●					"
55 +0.060 +0.030	70 "			●	●	●	●							+0.055 +0.025
60 "	74 "	●	●	●	●	●	●	●						"
60 "	75 "	●	●	●	●	●	●	●	●					"
63 "	75 "					●	●	●						"
65 "	80 "				●	●	●	●						"
70 "	85 +0.035 +0.013		●	●	●	●	●	●	●					+0.054 +0.024
70 "	90 "				●	●	●	●						"
75 "	90 "					●	●	●	●					"
75 "	95 "					●	●	●	●					"
80 "	96 "			●	●	●	●	●	●	●				"
80 "	100 "			●	●	●	●	●	●	●		●		"
90 +0.071 +0.036	110 "				●	●	●	●	●	●				+0.065 +0.030
100 "	120 "					●	●	●	●	●		●		"
110 "	130 +0.040 +0.015								●	●	●			+0.064 +0.029
120 "	140 "								●	●	●		●	"
125 +0.083 +0.043	145 "									●	●			+0.076 +0.038
130 "	150 "									●		●		"
140 "	160 "									●			●	"
150 "	170 "									●	●	●	●	"
160 "	180 "									●	●	●	●	"
170 "	190 "									●	●	●	●	"
180 "	200 "									●	●	●	●	"
190 +0.096 +0.050	210 "									●	●	●	●	+0.088 +0.042
200 "	230 "									●	●	●	●	"

How to order: Code d D L
 订单方式: JDB 08 10 12

可专门定制规格尺寸及材料
 装压后内孔公差值仅作参考!